

Revision Date: 12/12/2013

GALDEN® HT LOW-BOILING (1)

1. PRODUCT AND COMPANY IDENTIFICATION

.1. Identification of the substance or mixture		
Product name	: GALDEN® HT LOW-BOILING (1)	
Product grade(s)	: HT55; HT70	
Molecular weight	:	
Range of values :	340 - 410	
1.2. Use of the Substance/Mixture		
Recommended use	: - Heat transfer medium	
	 For industrial use only. 	
1.3. Company/Undertaking Identification		
Address	: SOLVAY SPECIALTY POLYMERS USA, LLC	
	4500 McGINNIS FERRY ROAD	
	ALPHARETTA GA 30005-3914 USA	
1.4. Emergency and contact teleph		
Emergency telephone number	: 1 (800) 424-9300 CHEMTREC ® (USA & Canada)	
Contact telephone number (product information):	: (856) 853-8119 (Product information)	

2. HAZARDS IDENTIFICATION

2.1. Emergency Overview:

NFPA	-	:	H= 1	F= 0	l= 0
General I	nformation				
	Appearance	:	liquid		
	Colour	:	colour	less	
	Odour	:	odourl	ess	

Main effects

- Not hazardous in normal conditions of handling and use -
- Ecological injuries are not known or expected under normal use.
- Thermal decomposition can lead to release of toxic and corrosive gases.

2.2. Potential Health Effects:

Inhalation

No known effect. -

Eye contact



Revision Date: 12/12/2013

- Contact with eyes may cause irritation.
- Redness

Skin contact

- Symptoms: Redness, Irritation.

Ingestion

- Ingestion may provoke the following symptoms:
- Symptoms: Nausea, Vomiting, Diarrhoea.

Other toxicity effects

See section 11: Toxicological Information

2.3. Environmental Effects:

See section 12: Ecological Information

3. COMPOSITION/INFORMATION ON INGREDIENTS

•

Perfluorinated polyether

CAS-No.

Proprietary %

4. FIRST AID MEASURES

4.1. Inhalation

- Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.
- Oxygen or artificial respiration if needed.

4.2. Eye contact

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- If eye irritation persists, consult a specialist.

4.3. Skin contact

- Wash off with soap and water.

4.4. Ingestion

- Drink 1 or 2 glasses of water.
- Do NOT induce vomiting.
- If symptoms persist, call a physician.

5. FIREFIGHTING MEASURES

5.1. Suitable extinguishing media

- Water
- powder
- Foam
- Dry chemical
- Carbon dioxide (CO2)



Revision Date: 12/12/2013

5.2. Extinguishing media which shall not be used for safety reasons

None.

5.3. Special exposure hazards in a fire

- The product is not flammable.
- Not explosive
- In case of fire hazardous decomposition products may be produced such as: Gaseous hydrogen fluoride (HF), Fluorophosgene

5.4. Hazardous decomposition products

- Gaseous hydrogen fluoride (HF).
- Fluorophosgene

5.5. Special protective equipment for firefighters

- Wear self-contained breathing apparatus and protective suit.
- When intervention in close proximity wear acid resistant over suit.

5.6. Other information

- Evacuate personnel to safe areas.
- Approach from upwind.
- Protect intervention team with a water spray as they approach the fire.
- Keep containers and surroundings cool with water spray.
- Keep product and empty container away from heat and sources of ignition.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

- 6.1.1. Advice for non-emergency personnel
 - Prevent further leakage or spillage if safe to do so.

6.1.2. Advice for emergency responders

- Ensure adequate ventilation.
- Material can create slippery conditions.
- Sweep up to prevent slipping hazard.
- Keep away from open flames, hot surfaces and sources of ignition.

6.2. Environmental precautions

- Should not be released into the environment.
- The product should not be allowed to enter drains, water courses or the soil.
- In case of accidental release or spill, immediately notify the appropriate authorities if required by Federal, State/Provincial and local laws and regulations.

6.3. Methods and materials for containment and cleaning up

- Soak up with inert absorbent material.
- Suitable material for picking up
- Dry sand
- Earth
- Shovel into suitable container for disposal.



Revision Date: 12/12/2013

6.4. Reference to other sections

- Refer to protective measures listed in sections 7 and 8.

7. HANDLING AND STORAGE

7.1. Handling

- Ensure adequate ventilation.
- Use personal protective equipment.
- Keep away from heat and sources of ignition.
- To avoid thermal decomposition, do not overheat.
- Take measures to prevent the build up of electrostatic charge.
- Clean and dry piping circuits and equipment before any operations.
- Ensure all equipment is electrically grounded before beginning transfer operations.

7.2. Storage

- No special storage conditions required.
- Keep away from heat and sources of ignition.
- Keep in properly labelled containers.
- Keep away from combustible material.
- Keep away from incompatible products

7.3. Packaging material

- glass
- Plastic material

7.4. Other information

- Provide tight electrical equipment well protected against corrosion.
- Refer to protective measures listed in sections 7 and 8.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Exposure Limit Values

Remarks:

Threshold limit values of by-products from thermal decomposition

Hydrogen fluoride anhydrous

- <u>US. ACGIH Threshold Limit Values</u> 03 2013 time weighted average = 0.5 ppm Remarks: as F
- <u>US. ACGIH Threshold Limit Values</u> 03 2013
 Ceiling Limit Value = 2 ppm
 Remarks: as F
- <u>US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989</u> time weighted average = 3 ppm Remarks: as F
- <u>US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989</u>
 Short term exposure limit = 6 ppm
 Remarks: as F



Revision Date: 12/12/2013

US. ACGIH Threshold Limit Values 03 2013 Remarks: as F, Can be absorbed through skin. US. OSHA Table Z-2 (29 CFR 1910.1000) 02 2006 time weighted average = 3 ppmUS. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) 02 2006 Permissible exposure limit = 2.5 mg/m3Remarks: as F US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008 time weighted average = 3 ppmRemarks: as F US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008 Short term exposure limit = 6 ppmRemarks: as F Carbonvl difluoride US. ACGIH Threshold Limit Values 03 2013 time weighted average = 2 ppmUS. ACGIH Threshold Limit Values 03 2013 Short term exposure limit = 5 ppmUS. OSHA Table Z-1-A (29 CFR 1910.1000) 1989 time weighted average = 2 ppmtime weighted average = 5 mg/m3US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989 Short term exposure limit = 5 ppmShort term exposure limit = 15 mg/m3US. OSHA Table Z-2 (29 CFR 1910.1000) 02 2006 time weighted average = 2.5 mg/m3 Remarks: Dust US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) 02 2006 Permissible exposure limit = 2.5 mg/m3Remarks: as F US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008 time weighted average = 2 ppmtime weighted average = 5 mg/m3US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008 Short term exposure limit = 5 ppmShort term exposure limit = 15 mg/m3ACGIH® and TLV® are registered trademarks of the American Conference of Governmental Industrial Hygienists.

SAEL = Solvay Acceptable Exposure Limit, Time Weighted Average for 8 hour workdays. No Specific TLV STEL (Short Term Exposure Level) has been set. Excursions in exposure level may exceed 3 times the TLV TWA for no more than a total of 30 minutes during a workday and under no circumstances should they exceed 5 times the TLV TWA.

8.2. Engineering controls

- Provide local ventilation appropriate to the product decomposition risk (see section 10).
- Refer to protective measures listed in sections 7 and 8.
- Apply technical measures to comply with the occupational exposure limits.



Revision Date: 12/12/2013

 For additional information, consult the current edition of The Guide to the Safe Handling of Fluoropolymers published by the Society of Plastics Industry, Inc. (SPI) Fluoropolymer Division.

8.3. Personal protective equipment

8.3.1. Respiratory protection

- No personal respiratory protective equipment normally required.
- Use respirator when performing operations involving potential exposure to vapour of the product.
- Use only respiratory protection that conforms to international/ national standards.
- Use NIOSH approved respiratory protection.
- Comply with OSHA respiratory protection requirements.

8.3.2. Hand protection

- Latex gloves
- Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

8.3.3. Eye protection

- Safety glasses with side-shields
- If splashes are likely to occur, wear: Tightly fitting safety goggles
- Protective goggles/face shield, if appropriate.

8.3.4. Skin and body protection

- Long sleeved clothing
- Safety shoes

8.3.5. Hygiene measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- When using, do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. General Information

Appearance	:	liquid
Colour	:	colourless
Odour	:	odourless

9.2. Important health safety and environmental information

Boiling point/boiling range	:	55 - 70 °C(131 - 158 °F)
Flash point	:	Remarks: The product is not flammable.
Flammability	:	Remarks: The product is not flammable.
Explosive properties	:	<u>Explosion danger</u> : <i>Remarks</i> : Not explosive



Revision Date: 12/12/2013

Oxidizing properties	:	Remarks: Non oxidizer
Vapour pressure	:	188 - 300 hPa
Relative density / Density	:	1.65 - 1.68 g/cm3 <i>Temperatur</i> e: 25 °C(77 °F)
Solubility(ies)	•	Water <i>Remarks</i> : insoluble fluorinated solvents <i>Remarks</i> : insoluble
Viscosity	:	ca. 0.75 - 0.85 mPa.s
9.3. Other data		
Melting point/range	:	Remarks: not applicable
Decomposition temperature	:	> 290 °C(554 °F)

10. STABILITY AND REACTIVITY

10.1. Stability

- Stable under recommended storage conditions.
- Metals promote and lower decomposition temperature
- In presence of titanium and its alloys the decomposition temperature decreases to 260°C.

10.2. Conditions to avoid

- Avoid to use in presence of high voltage electric arc and in absence of oxygen.
- Keep away from flames.
- To avoid thermal decomposition, do not overheat.

10.3. Materials to avoid

Combustible material, Flammable materials, non-aqueous alkalis, Lewis acids (Friedel-Crafts) above 100°C, Aluminum and magnesium in powder form above 200°C

10.4. Hazardous decomposition products

- Gaseous hydrogen fluoride (HF)., Fluorophosgene

11. TOXICOLOGICAL INFORMATION

Toxicological data

Acute oral toxicity

LD50, rat, > 5,000 mg/kg

Acute inhalation toxicity

LC50, rat, > 1,826 mg/l

Acute dermal irritation/corrosion



Revision Date: 12/12/2013

- LD50, rat, > 2,000 mg/kg

Skin irritation

rabbit, No skin irritation

Eye irritation

rabbit, No eye irritation

Sensitisation

guinea pig, Did not cause sensitisation on laboratory animals.

Genetic toxicity in vitro

- Not mutagenic in Ames Test.
- Chromosome aberration test in vitro, negative

Remarks

- Description of possible hazardous to health effects is based on experience and/or toxicological characteristics of several components.
- The product is biologically inert.
- Thermal decomposition can lead to release of toxic and corrosive gases.
- Exposure to decomposition products
- Causes severe irritation of eyes, skin and mucous membranes.

12. ECOLOGICAL INFORMATION

12.1. Ecotoxicity effects

Chronic toxicity

Remarks: no data available

12.2. Mobility

- Remarks: no data available

12.3. Persistence and degradability

Abiotic degradation

- Result: no data available

Biodegradation

Remarks: no data available

12.4. Bioaccumulative potential

- Result: no data available

12.5. Other adverse effects

- no data available

12.6. Remarks

- Ecological injuries are not known or expected under normal use.

13. DISPOSAL CONSIDERATIONS

13.1. Waste from residues / unused products



Revision Date: 12/12/2013

- Do not dump into any sewers, on the ground, or into any body of water. All disposal methods must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations.
- Waste characterizations and compliance with applicable laws and regulations are the responsibility of the waste generator.
- Can be incinerated, when in compliance with local regulations.
- The incinerator must be equipped with a system for the neutralisation or recovery of HF.

13.2. Packaging treatment

- Empty containers can be landfilled, when in accordance with the local regulations.

13.3. RCRA Hazardous Waste

- Listed RCRA Hazardous Waste (40 CFR 302) - No

14. TRANSPORT INFORMATION

- Sea (IMO/IMDG)
- not regulated
- Air (ICAO/IATA)
- not regulated
- U.S. Dept of Transportation
- not regulated
- It is recommended that ERG Guide number 111 be used for all non-regulated material.
- Canadian Transportation of Dangerous Goods
- not regulated

15. REGULATORY INFORMATION

15.1. Inventory Information

: - Listed on inventory.
: - Listed on inventory.
: - Listed on inventory.
: - Listed on inventory.
: - Listed on inventory.
: - Listed on inventory.
: - Listed on inventory.
: - Listed on inventory.



Revision Date: 12/12/2013

Chemicals and Chemical Substances (PICCS)		
New Zealand. Inventory of Chemicals (NZIOC)	Listed on inventory.	
Taiwan. National Existing Chemical Substance Inventory (NECSI)	Listed on inventory.	
EU. European Registration, Evaluation, Authorisation and Restriction of Chemical (REACH)	If product is purchased fr REACH, if not please cor	om Solvay in Europe it is in compliance with tact the supplier

15.2. Other regulations

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

- not regulated.

SARA Hazard Designation (SARA 311/312)

- Acute Health Hazard: No.
- Chronic Health Hazard: No.
- Fire Hazard: No.
- Reactivity Hazard: No.
- Sudden Release of Pressure Hazard: No.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

- not regulated.
- US. EPA CERCLA Hazardous Substances (40 CFR 302)
 - not regulated.

US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

- not regulated.

US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323) - not regulated.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

- This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm..

OSHA Hazard communication standard

This material is non-hazardous as defined by the American OSHA Hazard Communication Standard.

15.3. Classification and labelling

Canada. Canadian Environmental Protection Act (CEPA). WHMIS Ingredient Disclosure List (Can. Gaz., Part II, Vol. 122, No. 2)

- NOCONTPROD - Does not contain a controlled product



Material Safety Data Sheet North American Version

GALDEN® HT LOW-BOILING (1)

Revision Date: 12/12/2013

Remarks: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

EC Label - According to Regulation (EC) 1272/2008, as amended

No labelling

16. OTHER INFORMATION

Ratings :

NFPA (National Fire Protection Association)

Health = 1 Flammability = 0 Instability = 0

Further information

- New (SDS)
 - Distribute new edition to clients

Material Safety Data Sheets contain country specific regulatory information; therefore, the MSDS's provided are for use only by customers of the company mentioned in section 1 in North America. If you are located in a country other than Canada, Mexico or the United States, please contact the Solvay Group company in your country for MSDS information applicable to your location.

The previous information is based upon our current knowledge and experience of our product and is not exhaustive. It applies to the product as defined by the specifications. In case of combinations or mixtures, one must confirm that no new hazards are likely to exist. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and integrity of the work environment. (Unless noted to the contrary, the technical information applies only to pure product).

To our actual knowledge, the information contained herein is accurate as of the date of this document. However, neither the company mentioned in section 1 nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this information or its use. This information is for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. The user alone must finally determine suitability of any information or material for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. This information gives typical properties only and is not to be used for specification purposes. The company mentioned in section 1 reserves the right to make additions, deletions or modifications to the information at any time without prior notification.



Material Safety Data Sheet North American Version

GALDEN® HT LOW-BOILING (1)

Revision Date: 12/12/2013

Trademarks and/or other products of the company mentioned in section 1 referenced herein are either trademarks or registered trademarks of the company mentioned in section 1 or its affiliates, unless otherwise indicated.

Copyright 2011, Company mentioned in Section 1. All Rights Reserved.

